

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 017 197 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
21.08.2002 Bulletin 2002/34

(51) Int Cl.7: **H04L 12/28, H04L 29/06**

(43) Date of publication A2:
05.07.2000 Bulletin 2000/27

(21) Application number: **99125057.2**

(22) Date of filing: **15.12.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Pinard, Patrick**
Santa Clara, CA 95051 (US)
• **Kawaguchi, Dean**
San Jose, CA 95124 (US)

(30) Priority: **29.12.1998 US 222126**

(71) Applicant: **SYMBOL TECHNOLOGIES, INC.**
Holtsville, New York 11742-1300 (US)

(74) Representative: **Wagner, Karl H., Dipl.-Ing. et al**
WAGNER & GEYER
Patentanwälte
Gewürzmühlstrasse 5
80538 München (DE)

(54) **Data rate algorithm for use in wireless local area networks**

(57) A communications network comprising a wireless local area network includes a plurality of access points connected to a host computer and each other, and a plurality of mobile units with each mobile unit being arranged for association with at least one access

point. The mobile units are arranged to periodically scan for and identify the most eligible access point for association at the highest data rate on the basis of a performance criteria at the current data rate.

EP 1 017 197 A3

BEST AVAILABLE COPY



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 12 5057

| DOCUMENTS CONSIDERED TO BE RELEVANT | | | |
|--|--|--|--|
| Category | Citation of document with indication, where appropriate, of relevant passages | Relevant to claim | CLASSIFICATION OF THE APPLICATION (Int.Cl.7) |
| X | WO 97 21294 A (AIRNET WIRELESS COMMUNICATION) 12 June 1997 (1997-06-12) * abstract * * figures 2,3B,4A,4B,5 * * page 6, line 24 - page 7, line 2 * * page 13, line 3-16 * * page 19, line 6 - page 20, line 28 * * page 22, line 3-14 * * page 31, line 12 - page 32, line 24 * * page 32, line 18 - page 33, line 26 * * page 35, line 4 - page 36, line 20 * --- | 1-10 | H04L12/28 H04L29/06 |
| X | WO 94 27382 A (NORAND CORP) 24 November 1994 (1994-11-24) * abstract * * figures 1C,3A,3B,16A,16B * * page 26, line 3 - page 27, line 19 * * page 33, line 1 - page 35, line 7 * * page 52, line 8 - page 54, line 8 * * page 91, line 22 - page 92, line 18 * * page 105, line 7 - page 107, line 4 * --- | 1-10 | |
| X | WO 98 03030 A (NOKIA MOBILE PHONES LTD ;JOKINEN HARRI (FI); HAKASTE MARKUS (FI);) 22 January 1998 (1998-01-22) * abstract * * figure 2 * * page 4, line 32 - page 5, line 37 * * page 7, line 36 - page 8, line 31 * | 10 | |
| A | --- | 1-9 | |
| A,D | US 5 815 811 A (SYMBOL TECHNOLOGIES INC; HEIMAN FREDERIC ET AL) 29 September 1998 (1998-09-29) * abstract * * figure 2A * * column 1, line 36-46 * * column 2, line 29 - column 3, line 58 * --- | 1-10 | |
| | | -/-- | |
| The present search report has been drawn up for all claims | | | |
| Place of search MUNICH | | Date of completion of the search 26 June 2002 | Examiner Gabriel, C |
| CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document | | T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document | |

EPO FORM 1503 (03.02) (P4/C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 12 5057

DOCUMENTS CONSIDERED TO BE RELEVANT

| Category | Citation of document with indication, where appropriate, of relevant passages | Relevant to claim | CLASSIFICATION OF THE APPLICATION (Int.Cl.7) |
|--|---|-------------------|--|
| A | <p>VERMEER V: "Wireless LANs;why IEEE 802.11 DSSS?"</p> <p>WESCON/97. CONFERENCE PROCEEDINGS SANTA CLARA, CA, USA 4-6 NOV. 1997, NEW YORK, NY, USA,IEEE, US,</p> <p>4 November 1997 (1997-11-04), pages 172-178, XP010254380</p> <p>ISBN: 0-7803-4303-4</p> <p>* abstract *</p> <p>* page 172, right-hand column, line 8 - page 173, left-hand column, line 18 *</p> <p>-----</p> | 1-10 | |
| | | | TECHNICAL FIELDS SEARCHED (Int.Cl.7) |
| | | | |
| The present search report has been drawn up for all claims | | | |
| Place of search | Date of completion of the search | Examiner | |
| MUNICH | 26 June 2002 | Gabriel, C | |
| <p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone</p> <p>Y : particularly relevant if combined with another document of the same category</p> <p>A : technological background</p> <p>O : non-written disclosure</p> <p>P : intermediate document</p> <p>T : theory or principle underlying the invention</p> <p>E : earlier patent document, but published on, or after the filing date</p> <p>D : document cited in the application</p> <p>L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p> | | | |

EPO FORM 1803 03.82 (F04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 12 5057

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-06-2002

| Patent document cited in search report | | Publication date | | Patent family member(s) | Publication date |
|---|---|---------------------|----|----------------------------|---------------------|
| WO 9721294 | A | 12-06-1997 | US | 5950124 A | 07-09-1999 |
| | | | AU | 710939 B2 | 30-09-1999 |
| | | | AU | 1328997 A | 27-06-1997 |
| | | | CA | 2210792 A1 | 12-06-1997 |
| | | | EP | 0812503 A2 | 17-12-1997 |
| | | | JP | 10511835 T | 10-11-1998 |
| | | | WO | 9721294 A2 | 12-06-1997 |
| | | | US | 6132306 A | 17-10-2000 |
| | | | US | 6128512 A | 03-10-2000 |
| ----- | | | | | |
| WO 9427382 | A | 24-11-1994 | US | 5555276 A | 10-09-1996 |
| | | | AU | 6987694 A | 12-12-1994 |
| | | | CA | 2162722 A1 | 24-11-1994 |
| | | | WO | 9427382 A1 | 24-11-1994 |
| | | | US | 5696903 A | 09-12-1997 |
| | | | US | 5657317 A | 12-08-1997 |
| | | | US | 5790536 A | 04-08-1998 |
| | | | US | 5949776 A | 07-09-1999 |
| | | | AU | 696841 B2 | 17-09-1998 |
| | | | AU | 5986994 A | 19-07-1994 |
| | | | EP | 0681762 A1 | 15-11-1995 |
| | | | US | 5682379 A | 28-10-1997 |
| | | | CA | 2184811 A1 | 08-09-1995 |
| | | | WO | 9524074 A1 | 08-09-1995 |
| | | | US | 5726984 A | 10-03-1998 |
| | | | US | 5912926 A | 15-06-1999 |
| ----- | | | | | |
| WO 9803030 | A | 22-01-1998 | FI | 962834 A | 13-01-1998 |
| | | | AU | 3445397 A | 09-02-1998 |
| | | | EP | 0976282 A1 | 02-02-2000 |
| | | | WO | 9803030 A1 | 22-01-1998 |
| | | | JP | 2000514624 T | 31-10-2000 |
| | | | US | 6181686 B1 | 30-01-2001 |
| ----- | | | | | |
| US 5815811 | A | 29-09-1998 | US | 5528621 A | 18-06-1996 |
| | | | US | 5280498 A | 18-01-1994 |
| | | | US | 5142550 A | 25-08-1992 |
| | | | US | 5029183 A | 02-07-1991 |
| | | | CA | 2186923 A1 | 28-04-1997 |
| | | | EP | 0781005 A1 | 25-06-1997 |
| | | | JP | 9215044 A | 15-08-1997 |
| | | | US | 6002918 A | 14-12-1999 |
| | | | AU | 667264 B2 | 14-03-1996 |
| | | | AU | 5931994 A | 13-10-1994 |
| | | | CA | 2119335 A1 | 09-10-1994 |
| | | | EP | 0619663 A2 | 12-10-1994 |

EPO FORM P468

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 12 5057

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-06-2002

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|---|---------------------|----------------------------|---------------------|
| US 5815811 A | JP | 7099500 A | 11-04-1995 |
| | AT | 178748 T | 15-04-1999 |
| | AU | 657149 B2 | 02-03-1995 |
| | AU | 2089992 A | 03-06-1993 |
| | CA | 2072345 A1 | 28-05-1993 |
| | DE | 69228856 D1 | 12-05-1999 |
| | DE | 69228856 T2 | 11-11-1999 |
| | EP | 0544337 A1 | 02-06-1993 |
| | ES | 2130147 T3 | 01-07-1999 |
| | JP | 5244158 A | 21-09-1993 |
| | US | 5479441 A | 26-12-1995 |
| | US | 5668803 A | 16-09-1997 |
| | AT | 168845 T | 15-08-1998 |
| | CA | 2051212 A1 | 29-06-1992 |
| | DE | 69129838 D1 | 27-08-1998 |
| | DE | 69129838 T2 | 25-03-1999 |
| | EP | 0496986 A2 | 05-08-1992 |
| | EP | 0797332 A2 | 24-09-1997 |
| | ES | 2118733 T3 | 01-10-1998 |
| | JP | 4304049 A | 27-10-1992 |
| | US | 5401944 A | 28-03-1995 |
| | AU | 627333 B2 | 20-08-1992 |
| | AU | 5808090 A | 03-01-1991 |
| | CA | 1310370 A1 | 17-11-1992 |
| | DE | 69030936 D1 | 24-07-1997 |
| | DE | 69030936 T2 | 29-01-1998 |
| | EP | 0405074 A2 | 02-01-1991 |
| | EP | 0770962 A2 | 02-05-1997 |
| | JP | 2506481 B2 | 12-06-1996 |
| | JP | 3038133 A | 19-02-1991 |
| | US | 5157687 A | 20-10-1992 |
| | US | 5103461 A | 07-04-1992 |
| ----- | | | |

EPO FORM PD459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 017 197 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

05.07.2000 Bulletin 2000/27

(51) Int. Cl.⁷: **H04L 12/28, H04L 29/06**

(21) Application number: **99125057.2**

(22) Date of filing: **15.12.1999**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: **29.12.1998 US 222126**

(71) Applicant:

**SYMBOL TECHNOLOGIES, INC.
Holtsville, New York 11742-1300 (US)**

(72) Inventors:

- **Pinard, Patrick
Santa Clara, CA 95051 (US)**
- **Kawaguchi, Dean
San Jose, CA 95124 (US)**

(74) Representative:

**Wagner, Karl H., Dipl.-Ing. et al
WAGNER & GEYER
Patentanwälte
Gewürzmühlstrasse 5
80538 München (DE)**

(54) **Data rate algorithm for use in wireless local area networks**

(57) A communications network comprising a wireless local area network includes a plurality of access points connected to a host computer and each other, and a plurality of mobile units with each mobile unit being arranged for association with at least one access point. The mobile units are arranged to periodically scan for and identify the most eligible access point for association at the highest data rate on the basis of a performance criteria at the current data rate.

EP 1 017 197 A2

Description

REFERENCE TO RELATED APPLICATIONS:

[0001] This application is a continuation-in part of application Serial No. 08/747,034 filed November 8, 1996, which was a continuation in part of application Serial No. 08/549,051 filed Oct. 27, 1995, now U.S. Patent 5,815,811, which was a continuation-in-part of Serial No. 08/044,648, filed April 8, 1993, now U.S. Patent No. 5,528,621, which was a continuation-in part of Serial No. 07/799,172, filed November 27, 1991, now U.S. Patent No. 5,296,842, which was a continuation-in-part of application Serial No. 07/635,859, filed December 28, 1990, now U.S. Patent No. 5,142,550, which was a continuation-in-part of application Serial No. 07/374,452, filed June 29, 1989, now U.S. Patent No. 5,029,183.

BACKGROUND OF THE INVENTION:

1. Field of the Invention

[0002] The invention relates generally to wireless local area networks. In particular the invention relates to a local area wireless network with variable data transmission rates, including a plurality of mobile units roaming among access points operating at possibly different data rates.

2. Description of the Related Art.

[0003] Wireless local area networks (LANs) are used in business applications such as inventory, price verification mark-down, portable point of sale, order entry, shipping, receiving and package tracking. Wireless local area networks use infrared or radio frequency communications channels to communicate between portable or mobile computer units and stationary access points or base stations. These access points are in turn connected by a wired or wireless communication channel to a network infrastructure which connects groups of access points together to form a local area network, including, optionally, one or more host computer systems.

[0004] Wireless infrared and radio frequency (RF) protocols are known which support the logical interconnection of portable roaming terminals having a variety of types of communication capabilities to host computers. The logical interconnections are based upon an infrastructure in which at least some each of the remote terminals are capable of communicating with at least two of the access points when located within a predetermined range therefrom, each terminal unit being normally associated with and in communication with a single one of such access points. Based on the overall spatial layout, response time, and loading requirements of the network, different networking schemes and com-

munication protocols have been designed so as to most efficiently regulate the association of the mobile unit with specific access points, and the availability of the communication channel to individual mobile units for broadcasting.

[0005] One such protocol is described in U.S. Patent Nos. 5,029,183; 5,142,550; 5,280,498; and 5,668,803 each assigned to Symbol Technologies, Inc. and incorporated herein by reference.

[0006] Another such protocol is described in U.S. Patent 5,673,031. Still another protocol is set forth in the IEEE Standard 802.11 entitled "Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications" available from the IEEE Standards Department, Piscataway, NJ (hereinafter the "IEEE 802.11 Standard").

[0007] The IEEE 802.11 standard permits either infrared or RF communications, at 1 Mbps and 2 Mbps data rates, a medium access technique similar to carrier sense multiple access/collision avoidance (CSMA/CA), a power-save mode particularly important for battery-operated mobile units, seamless roaming in a full cellular network, high throughput operation, diverse antennae systems designed to eliminate "dead spots", and an easy interface to existing network infrastructures.

[0008] In Europe, the European Telecommunications Standards Institute (ETSI) has been working in parallel on a protocol standard entitled HIPERLAN (European High Performance LAN), for high data wireless network systems. The frequency spectrum for HIPERLAN in the 5 GHz and 17 GHz bands has been allocated by the European Conference of Postal and Telecommunications Administrations (CEPT), with a proposed data rate of over 20 Mbit/sec. The IEEE 802.11 Committee is also currently considering extensions to the IEEE 802.11 Standard providing for optional higher data rates as well.

[0009] The IEEE 802.11 Standard provides for these types of MAC frames-control, data, and management. All control frames are transmitted at one of the PHY mandatory rates, typically 1 Mbps, so that they will be understood by all stations. The other frames are transmitted at one of the rates in the basic rate set under the standard. The algorithm for performing rate switching is beyond the scope of the standard.

[0010] The term "roaming" relates to mobile units associating with different access points. Each mobile unit analyzes received signals from access points to identify and associate with an eligible access point. Analogous to cells in a cellular telephone network, the region around a given access point may also be referred to as a "cell". Roaming between cells provides great flexibility and is particularly advantageous in locations that are difficult to wire, for simple relocation of work stations, and for portable work stations.

[0011] Although the IEEE 802.11 Standard provides the basic packet types which enable roaming, it does not actually set the roaming algorithm. According

to the standard, the mobile unit determines the access point with which it will associate and the access point must accept the mobile unit unless the access point is defective or certain alarm conditions exist, such as memory full. There is, however, no suggestion of how, or by what criteria, other than those mentioned above, the mobile unit might select an appropriate access point, or an optimum access point.

SUMMARY OF THE INVENTION:

1. Objects of the Invention

[0012] It is an object of the present invention to implement a wireless local area network with multiple data transmission rates.

[0013] It is a further object of the present invention to provide an algorithm allowing selection by a mobile unit of an access point for association maximizing the data throughput.

[0014] It is still a further object of the present invention to provide a wireless communication system allowing roaming by a mobile unit over access points having different data rate characteristics.

2. Features of The Invention

[0015] According to the present invention, there is provided A method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, including the steps of evaluating the mobile unit performance; and if the mobile unit performance is below a threshold, scanning for the most eligible access point at predetermined intervals; and associating with the most eligible access point at the highest data rate.

[0016] If the mobile unit performance is below a threshold and after, scanning for the most eligible access point at predetermined intervals; and if the mobile unit is unable to associate with another access point at a higher data rate, reduce to data rate to the next lower data rate.

[0017] If the mobile unit performance is above a threshold, increasing the data rate of the mobile unit to the next highest data rate.

[0018] As a variant of such algorithm, there is provided a method in data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates, and capable of communicating with at least two access points in a predetermined range therefrom, including the steps to scanning for the most eligible access point at the highest available data rate; evaluating the received access point signal quality and performance at the highest data rate; associating

with the most eligible access point at the highest data rate if one is available; scanning for the most eligible access point at a second lower data rate if no association has been made; evaluating the received access point signal quality at the second data rate; and associating with the most eligible access point at the second data rate.

[0019] The present invention also provides a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, including means in the mobile unit to scan for the most eligible access point at predetermined intervals means in the mobile unit for evaluating the performance statistics at the current data rate; and means for associating with the most eligible access point at the highest data rate.

[0020] The novel features which are considered as characteristic of the invention are set forth in particular in the appended claims. The invention itself, however, both as to its construction and its method of operation, together with additional objects and advantages thereof, will best be understood from the following description of a specific embodiment, when read in conjunction with the accompanying drawings. It is to be understood that the invention may be carried into practice in a number of ways, and the described embodiment is not intended to be limiting.

BRIEF DESCRIPTION OF THE DRAWING:

[0021] The features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as other features and advantages thereof, may best be understood by reference to the detailed description of a specific embodiment which follows, when read in conjunction with the accompanying drawings, wherein:

Fig. 1 is a block diagram of a packet data communication system according to one embodiment of the invention;

Fig. 2 is timing diagram showing events (RF transmission) vs. time for a data transmission sequence in the system of Fig. 1;

Fig. 3 is a block diagram illustrating the steps carried out by a mobile unit during the rate adjusting and roaming process;

Fig. 4 shows a probe response message typically sent by an access point according to the present invention;

Fig. 5 is a flow chart illustrating the steps carried out

by a mobile unit for selection of the most eligible access point;

Fig. 6 shows, schematically, the functional elements that make up the mobile units shown in Fig. 1.

DETAILED DESCRIPTION OF A SPECIFIC EMBODIMENT:

[0022] Referring to Fig. 1, a data communications network according to one embodiment of the invention is illustrated. A first local area network 100 is illustrated, including a host processor 10 is connected by a wired communications link 11 to a number of stationery access points or base stations 12,13; other base stations 14 can be coupled to the host through the base stations or by an RF link. Each one of the base stations 12,13,14 is coupled by an RF link to a number of remote mobile units 15. In one embodiment, the remote mobile units 15 are hand-held, battery-operated data terminals or voice communication handsets such as described in U.S. Patent Nos. 5,029,183; Serial Nos. 08/794,782 filed February 3, 1997, and 09/008,710, filed January 16, 1998 all assigned to Symbol Technologies, Inc., and incorporated herein by reference.

[0023] Various other types of remote terminals may be advantageously employed in a system having features of the invention; these remote terminals ordinarily would include data entry facilities such as a magnetic card reader or the like, as well as a display (or printer) for indicating to a user information detected, transmitted and/or received by the terminal. In this embodiment used as an illustrative example, there may be from one up to sixty-four of the base stations (three stations being shown in the Figure) and up to several hundred of the remote units; of course, the network may be expanded by merely changing the size of address fields and the like in the digital system, as will appear, but a limiting factor is the RF traffic and attendant delays in waiting for a quiet channel.

[0024] The first LAN 100 may be coupled to additional LANs 200,300,400 etc. through controllers such as bridges 50,60, etc. or routers 55,65,75,85,95,105, etc. This communications network as seen in Fig. 1 would ordinarily be used in a manufacturing facility, office building complex, warehouse, retail establishment, or like commercial facility or combination of these facilities, where the data-gathering terminals would be used for inventory control in stockroom or receiving/shipping facilities, at checkout (point of sale) counters, for reading forms or invoices of the like, for personnel security checking at gates or other checkpoints, at time clocks, for manufacturing or process flow control, and many other such uses.

[0025] Although hand-held, laser scanning bar-code reader data terminals are mentioned, the data terminals may also include bar-code readers of the CCD or

wand type, and may be stationery rather than hand-held. The mobile units 15 may also be voice communication handsets, pagers, still image or video cameras; or any combination of the foregoing. Other types of data gathering devices may be utilized as terminals and use the features of the invention, such as temperature, pressure, or other environmental measuring devices, event counters, voice or sound activated devices, intrusion detectors, etc.

[0026] According to an important feature of one embodiment of the invention, an RF packet communications protocol is provided between the remote units and the base stations, and includes a transmit/receive exchange, referred to hereinafter simply as an "exchange". This protocol is similar to collision-sense multiple access (CSMA) in that a unit first listens before transmitting, and does not transmit if the channel is not free. As seen in Fig. 2, this exchange always begins with a remote-to-base transmitted packet, representing an RF transmission from a remote unit to be received by the base stations within range. The transmitted packet is followed after a fixed time interval by a base-to-remote unit of RF information transmitted by the base station servicing this particular remote unit. Each of these packets is of fixed timing; a transceiver in a remote unit begins an exchange at its own initiative by first listening for other traffic for a brief interval t_0 (typically 0.3 msec.) and, if the RF channel is quiet, starting a transmission at a time of its own selection (asynchronous to any clock period of the base stations or host computer). This outgoing transmission packet lasts for a time t_1 as seen in the Figure, and in an example embodiment this period is 4.8 milliseconds. Then at a precise time delay t_2 after it started transmission (e.g. 5 msec after the beginning of t_1) the transceiver begins listening for the return packet from the base station. The transceiver in the remote unit only responds to receipt of the packet beginning in a very rigid time window t_3 of a few microseconds length, and if the packet has not started during this window then anything to follow is ignored. The packet is an acknowledge signal, and also contains data if the base station has any message waiting to be sent.

[0027] The steps carried out by a mobile unit 15 which is not currently associated to an access point in selecting an access point are shown in highly simplified form in Fig. 3. In Fig. 3, the mobile unit (MU) (first noted at step 6) sends out a probe packet to all access points (APs), typically at the lowest data rate it is otherwise able to use with the network. The probe packet contains the mobile unit source address but has no destination address and hence any access point that detects the probe packet and is capable of responding at the same data rate must send a response. Accordingly, the probe packet is detected by all access points within range (step 7) and a subset of those access points sends out a probe response packet (step 8.) An evaluation of the signal quality and possibly other factors is made (as will

be subsequently described) by the MU of the communications with the most eligible access point (if any) at the highest data rate. If such communications are acceptable, the MU will associate with the selected AP (step 9).

[0028] If the MU is already associated with an access point and operating at a data rate lower than the highest data rate, then depending upon the performance statistics (to be described below), it will carry out an update probe at predetermined intervals to see if it can operate at a higher data rate, with a new AP. Such roaming to a new AP is typically encountered when the MU is moved in and out of range, e.g. to and from the periphery of the network of APs.

[0029] If the MU is already associated with an access point and operating at a data rate higher than the lowest data rate but experiencing poor performance, it will carry out an update probe at predetermined intervals to see if it can roam to another ALP at the same or higher data rate. Such roaming to a new AP is typically encountered when the MU is moved in and out of range, e.g. to and from the periphery of the networks of APs.

[0030] The form of the probe response packet is shown in Fig.4. The information contained therein includes the access point address, the hopping pattern, the present channel, time left in the present channel, and in other embodiments of the invention, optionally the loading factor (discussed in more detail below) and any other timing information that may be required. Returning to Fig. 3, the mobile unit considers the subset of available access points with which to associate based on an evaluation of the signal quality of the response packets that it receives.

[0031] Referring next to Fig. 5, at each data rate the mobile unit evaluates and considers the most eligible access point in the following manner:

[0032] As each probe packet response (PPR) is received 16 the signal quality of the response is measured by determining the received signal strength indication (RSSI) 17. For reference, RSSI values generally vary from 25 to 60, with good communications experienced above approximately 35. In practice, rather than relying on a single instantaneous value, the RSSI information for each access point along with other performance statistics is placed in a table in the memory of the mobile unit and is updated each time a probe response packet is received from that access point. In order to minimize fluctuation the RSSI value for each access point in the table is averaged over a predetermined number of responses. It has been found that large variations in the RSSI values for a given access point have been recorded even when measured by a stationary mobile unit, and averaging is used in order to reduce the range of values and minimize "slow thrashing". When "thrashing", a mobile unit associates with a first access point, then roams to a second access point after a short period of time and then further access points in a random manner without any long attachment to a single access point; the expression "slow thrashing" may be

interpreted accordingly. The averaging calculation may include the step of discarding values outside a given range, for example ten or more counts below the average RSSI value.

[0033] Once the RSSI values have been calculated, an "eligible group" of access points is selected 18, including all access points having an RSSI value no more than six counts below the best detected RSSI value. From that group the access point having the lowest load factor (LF) is determined 19, 20. The load factor is a measure of how many mobile units are currently associated with a given access point; in the present case the load factor is represented by a simple numerical value representing the exact number of associated mobile units. The access point thus selected is the most eligible access point and the mobile unit then selects that access point for association. If more than one access points within the eligible group exhibit the same load factor then, of those, the access point having the highest RSSI value is selected as the most eligible access point and the mobile unit associates with that access point.

[0034] The mobile units are programmed to carry out an update probe at predetermined intervals. In the present embodiment each mobile unit carries out a full scan, probing all seventy nine channels, upon power up and every thirty seconds. The probe response packet transmitted by an access point contains all necessary synchronization information for a mobile unit to latch on to the current channel of the access point and follow the hopping pattern at any stage. In an alternative arrangement the RSSI value for the access point is calculated not from the strength of the probe response signal but from the strength of the "beacon packet" issued by the access point. Each access point issues a beacon packet every 100 milliseconds containing, in addition to other information, timing information similar to that contained in the probe response packet. A slightly different approach is taken where a mobile unit is currently associated with an access point but at a communication level that is unsatisfactory. An unsatisfactory communication level may be identified, for example, when more than fifty percent retries, cyclic redundancy code (CRC) errors or missed beacons are detected. In that case the mobile unit will re-associate using the steps illustrated in Figs. 3 and 5 except that the access point with which the mobile unit was experiencing poor communications will be excluded from the eligible group of access points (see step 18 of Fig. 5). The ineligible access point can, however, in due course be re-admitted to the eligible group after a succession of acceptable RSSI values have been observed. It should be noted that a mobile unit experiencing poor communication will re-associate only if an eligible access point is identified.

[0035] In one embodiment, in cases where a mobile unit is not experiencing an unsatisfactory communications level (as defined above) it makes a roaming decision at predetermined times. Once again the steps

described above with reference to Fig. 6 are carried out, but with the following modifications:

1. The current access point is included in the eligible group if its RSSI value is no more than eleven counts below the best RSSI value.

2. When choosing the access point having the lowest loading factor in the group, access points having a loading factor which is more than 75% of the loading factor of the current access point loading factor are excluded.

[0036] The additional steps enable the mobile unit to avoid "frivolous roaming" that is to say, reassociation with new access points when the current access point is in fact satisfactory.

[0037] The system thus allows preemptive roaming providing for dynamic load balancing, that is a mobile unit may re-associate with a new access point although it is not experiencing poor communications with a current access point, but the newer access point will offer considerably improved communications. The possibility of a mobile unit losing contact with an access point altogether and experiencing periods where it is not communicating with any access points, may thus be avoided.

[0038] In addition, the system has been improved by adjusting the sensitivity so that a mobile unit will not tend to roam from a current associated access point to another at the rate that it would otherwise, where the signal strengths of various access points are similar in magnitude. Accordingly, greater stability is achieved.

[0039] In a further modification the probe packet may include an identification of the access point that the mobile unit is currently associated with for example, the BSS ID. Such an arrangement would be more reliable than the messages passed between access points relaying reassociated events.

Throughput Maximization

[0040] The overall goal of the dynamic rate control algorithm is to maximize throughput for each Mobile Unit (MU) operating within a wireless network containing multiple Access Points (APs). Two transmission rates are currently within the IEEE 802.11 Standard- 1 and 2 Mbits/seconds and we will use such two rates as examples in the discussion that follows. In full generality, however, the present invention is also applicable to systems with more than two rates. We assume that each MU is capable of more than one rate, but will have a "currently selected" transmission rate. Performance statistics are maintained by the MU while operating at a given rate; for example, percentage of transmission retries (i.e. no Acknowledge frame received following a transmission). When the performance statistics reach or exceed certain thresholds, a state change will occur in the MU in an attempt to maximize throughput

(KBytes/second of transferred data). The present invention attempts to maximize throughput in the following ways.

A. If at 2 Mbits/second and the performance statistics indicate "poor quality", the MU will attempt to roam from one AP to another in order to maintain the 2 Mbit/second performance. This roaming procedure is like that described below where RSSI and load leveling factors are considered in selecting the "best" AP. However, in addition, only APs which can support the 2 Mbits/second rate are eligible.

B. If at 2 Mbits/second and the performance statistics indicate "poor quality" and the MU was unable to roam to an AP which supports the 2 Mbit rate, reduce the "currently selected" rate from 2 to 1 Mbit/second and remain associated with the current AP. As described below, 1 Mbit/second transmissions have a greater range (distance between an MU and an AP) than 2 Mbit transmissions. The assumption is that the poor quality is due to range and that by dropping to 1 Mbit the retry rate will decrease and the overall throughput will increase.

C. If at 1 Mbits/second and the performance statistics indicate "good quality" and the MU has been at the 1 Mbit/second rate for a period sufficient to eliminate extremely rapid rate changes (thrashing), increase the "currently selected" rate from 1 to 2 Mbit/second. (Note that it is possible that the MU's position relative to the AP will once again result in poor 2 Mbit performance. If so the MU may subsequently be forced to fall back to 1 Mbit again, i.e. slow thrashing. However, if the MU is truly mobile, this condition will eventually change.)

Transmission Range and Transmission Rate

[0041] As noted above, MUs operating at 1 Mbit transmissions have a greater range than an MV operating at a 2 Mbit data transmission rate. To depict the consequence of this fact, imagine a figure depicting four Access Points and their respective ranges of coverage, both at 1 and 2 Mbit transmission rates. (Note that the effective range from an AP to an MU is assumed to be the same as the range from the MU to the AP.) Place the APs at the corners of a 4 inch square. Draw a circle around each AP with a tree inch radius. This is the range of "good performance" at 2 Mbits. Note that the circles overlap, indicating that an MU could travel about this four AP area and maintain good 2 Mbit performance. Now draw a second circle around each Access Point with a radius of 5 inches. This is the maximum range at the 1 Mbit rate. Obviously, users who want continual 2 Mbit performance will have to install Access Points and position them closer to one another to obtain the continuous 2 Mbit coverage. It is the feature of the

roaming algorithm of the present invention to roam to an AP in order to maintain 2 MBit coverage, when possible, rather than reduce the transmission rate in order to increase range. In addition, the combined roaming/dynamic rate control algorithm also has the provisions for increasing and decreasing transmission rates when roaming to maintain 2 MBit performance is not possible.

Poor 2 MBit Performance

[0042] According to the criteria in the preferred embodiment of the present invention, poor 2 MBit performance occurs when, while transmitting at 2 MBits, either of the following two conditions occurs:

A) The 2 MBit transmission retry rate is greater than or equal to 35% and there has been a statistically-significant number of transmission attempts (e.g. thirty) within a 10 second evaluation period.

B) Eight consecutive unsuccessful 2 MBit transmission attempts. (This criteria addresses the low traffic case.)

[0043] Of course, other similar or equivalent criteria can be used, or such criteria varied depending upon application or other performance considerations, and are within the scope of the present invention.

[0044] As noted above, when poor 2 MBit performance is encountered, an MU will first attempt to roam to an AP which will support continued 2 MBit performance and, if unsuccessful, will reduce its "currently selected" transmission rate to 1 MBit.

1. The first two transmission attempts for a given data frame will be tried at 2 MBits (when 2 MBits is the currently selected rate for data frame transmission). Tries 2 through N are tried at 1 MBit. This allows frames to "get through" until criteria A or B above is satisfied. This temporary reduction of rate does not change the "currently selected" rate of 2 MBit.

2. MUs periodically scan for Access Points by sending Probe frames and waiting for one or more Probe Response frames from APs which happen to be on the given frequency being probed. The Probe frames are normally sent at a 1 MBit rate; Probes will be sent at 2 MBits if an MU is configured to transmit only at 2 MBits. But the dynamic rate control algorithm is only used when an MU has the option of both transmission rates. The Probe Response frame contains a data structure which specifies the rates that the AP can support, as specified in the 802.11 Specification. This information is saved for each responding AP in an Access Point Table data structure and is subsequently

available to the roam algorithm for decision making.

3. When roaming away from an AP due to poor 2 MBit quality, the AP's current averaged RSSI is saved away in its corresponding Access Point Table entry. The AP will be ineligible to roam back to, when the reason for roaming is to maintain 2 MBit performance, until its averaged RSSI has increased by 3 RSSI counts. (An ongoing average RSSI is maintained for all APs which send Probe Responses to a given MU during its periodic scan/probing function.) This prevents frivolous roaming back to an AP with known poor performance at a given signal strength level. This is analogous to the 1 MBit poor quality RSSI threshold maintained for APs and described in the earlier patent applications. The expanded roaming algorithm maintains two poor quality RSSI values for an AP, one inhibiting roaming to the AP for 2 MBit performance and one inhibiting roaming to the AP even when 1 MBit performance would be acceptable.

Changing from 1 to 2 MBit/second:

[0045] An MU will change its "currently selected" rate from 1 to 2 MBits/second whenever one of the following criteria is met:

A) The 1 MBit transmission retry rate is less than 7% and there has been a statistically-significant number of transmission samples (e.g. thirty) within a 10 second evaluation period.

B) The 1 MBit transmission retry rate is less than 7% and the 1-MBit rate has been in effect for at least 30 seconds. (Addresses the low traffic situation.)

C) The cell has heavy traffic (500 frame detects within 10 seconds) and the 1 MBit rate has been in effect for at least 30 seconds. (Addresses the case where the 2 MBit retry rate is due to transmission collisions rather than range.)

Power Saving Features

[0046] The mobile units may incorporate a number of power-saving features, aimed at maximizing battery life. These features, known as "power-saving protocols" (PSP), will now be described in more detail, and are independent of the data rate control functionality.

[0047] The PSP can be described with reference to an expanded block diagram of a mobile unit 15 as shown in Fig. 6. Fig. 6 illustrates two sections of the MU, a radio section 30 and a terminal section 40.

[0048] The radio section 30 includes a transmitter/receiver radio 31 connected to an antennae 32. The radio is also connected to a circuit represented generi-

cally as ASIC 33, which may be a single IC or several, including a microprocessor, memory for storing firmware programs, static RAM, and/or application specific integrated circuits for performing a number of media level access (MAC) protocol functions and the MAC/PHY protocol interface.

[0049] In particular, the ASIC 33 will perform the function of recognizing the data rate of the incoming broadcast signals received by the radio 31, and processing such signals at the appropriate data rate. More specifically, in the context of the 802.11 Standard, this would include parsing of the packet header for the bit rate field.

[0050] The ASIC 33 also functions to implement the data rate algorithm described above and in Figures 4 and 5.

[0051] The terminal section 40 includes an interface 41 to the radio section 30, and a battery 48 which powers both the terminal section 40 and the radio section 30. The terminal section 40 typically includes a data entry keypad, touch screen, or keyboard 42, a display 43, CPU (including stored program memory) 44, and optionally a microphone 45, speaker 46, and CODEC/DSP circuitry 47 for voice processing to allow the mobile unit 15 terminal to provide voice communication capability.

[0052] The PSP makes use of a number of different algorithms, all of which are based on the approach of turning off the radio and CPU, both of which consume a considerable amount of power, and halting the ASIC clock in the radio section 30 while waiting for the next message from the access point. It will be recalled that the basic message control system is defined in IEEE 802.11 protocol specification, and involves the use of beacon messages with traffic indicator maps and a poll message to request transmission of the data.

[0053] The various PSP algorithms are defined in such a way as to allow a user-definable tradeoff between performance and the level of power saving.

[0054] The first algorithm is a static algorithm that wakes up the radio 31 just in time to receive every broadcast beacon. Even though the ASIC clock in the radio section has been powered down, the system still maintains a record of the time using the CMOS clock 35, which is powered by its own miniature battery 36. A similar second algorithm wakes up the radio 31 in time to receive every other beacon. Similarly, algorithms 3 to 10 switch on the radio in time to receive, respectively, every third to every tenth beacon.

[0055] Another algorithm known as "algorithm number 11" is dynamic, and permits the wakeup signals to be based on the actual message traffic. Whenever the radio 31 sends a message, or whenever it receives a message, it sets the wakeup interval to a minimum value (usually to wake up in time to receive each expected beacon.) This provides for a fast response as long as the traffic is continuous, or almost so. If no activity is detected, the algorithm provides for the wakeup

interval to be gradually reduced, typically linearly, up to a maximum value of 10; in other words, at that point the radio is woken up just in time to receive every tenth beacon. Alternatively, instead of the delay increasing linearly (intervals of 1,2,3...), the algorithm may remain on maximum for a predefined period, with the delay increasing to a maximum value only once that period has been reached.

[0056] Yet a further algorithm, known as algorithm number 12, provides for even higher performance. In this algorithm, a record is kept of message traffic (based for example on the number of payload bytes or on the number of messages), and when a threshold is exceeded the radio is then switched into continuous mode. As long as significant traffic is being processed. Either outgoing or incoming, the radio will stay in continuous mode. However, if the traffic falls below the predefined threshold for a certain number of second (for example, five seconds) the system then reverts back to algorithm number 11.

[0057] For all of the algorithms previous mentioned, the time of the next beacon is of course precisely known, and may be computed so that the radio can be turned on just in time to receive the beacon. If the beacon is displayed in the access point 5 (due for example to pre-existing traffic), then the radio 31 will stay awake for some predefined period of time to ensure that the beacon is received.

[0058] Preferably, all mobile units respect the expected time of the beacon and do not transmit messages that might cause the timing of the beacon to be delayed.

[0059] If a mobile unit misses a beacon (either because it is not heard, or because it is received with an error), then the unit automatically schedules a wakeup for the next beacon, even if it would not normally expect to wake-up for that particular beacon based on the current algorithm in use. This permits fast recovery from message errors, and also helps to detect that the access point 5 is or is not transmitting beacons in a minimum amount of time.

[0060] The mobile unit is capable of going into a number of operating states or modes for managing the status of the radio 31 and the interface to the terminal. To minimize power, the radio 31 is turned on only if radio activity is required, even though the radio station 30 itself may need to be powered up to allow communications with the terminal section 40. If the radio section 30 powers up to communicate with the terminal section, and it becomes time to receive or to transmit a message, then the radio 31 is automatically powered up. Whenever the radio is no longer needed, but the interface 34 remains active, the radio may be powered down in order to save power. When the radio section 30 has no requirement to communicate either via the interface 34 or via the antennae 32, all elements of the radio are powered down, as is the ASIC 33. The system then awaits a wakeup call either from the beacon timer asso-

ciated with the clock 35 or from the terminal section 40 (for example, because the user has activated the data entry 42).

[0061] If the mobile unit is unassociated with an access point, it may remain in power save mode. In that mode, it automatically wakes up to search for an access point periodically (for example every second), thereby minimizing use of power but still providing a reasonable capability of finding an access point with which the unit can associate fairly rapidly. Once the mobile unit has associated with an access point, it needs to wake up only in order to receive beacon messages.

[0062] The mobile unit preferable provides close coupling between the radio section 30 and the terminal section 40, in order to provide appropriate network support with minimum power usage. The units typically have an active mode (either full power or power-save mode), a suspend mode (all unnecessary items are off but the CPU can resume at any time), and a power-off mode (minimum power, with no internal activity except for the CMOS clock 35, but still able to resume from where it left off before the power was cut.)

[0063] The radio section 30 is tightly integrated with the terminal section 40 in several ways, thereby permitting joint power saving modes. Firstly, the radio section may be set to remain in its prescribed operating mode whenever the terminal section 40 is active. Second, when the terminal section 40 goes into suspend mode, the radio section 30 is placed in a low power mode automatically. This may for example be the PSP algorithm number 10, described above. In this mode, the radio section is capable of receiving messages directed to the terminal section 40. Options exist to allow either directed packets only, or directed and broadcast/multicast packets. These options allow the customization of the network to minimize the power by minimizing wakeup events. When a qualified packet is received, the radio section 30 places the data in a buffer within RAM (not shown) and wakes up the terminal section 40. As the terminal section may require some time to wake up, radio section 30 may buffer received packets until such time as the terminal section 40 is able to process them.

[0064] While in the suspend mode, the radio section 30 has the option of powering itself down if no activity has been detected for a programmable amount of time, for example 1 hour. This allows a mobile unit that has been left inactive, or has gone out of range, to limit battery consumption to a reasonable amount.

[0065] If the terminal has been turned "off" (left in a powered but fully inactive state), the radio section 30 is automatically put to sleep, the lowest level of power consumption. In this mode, it does not respond to messages or to wakeup commands. When the terminal section 40 is then powered up ("Resume"), the radio section 30 itself the automatically powers up and resumes form its present state.

[0066] If the terminal section 40 loses power (for example, if the battery 48 is removed), the radio section

30 is automatically switched off or otherwise powered down. In that mode, the battery 36 may act as a backup battery, able to sustain the operating state of the terminal section. Alternatively, a separate backup battery (not shown) may be provided. When the battery 48 is reinserted or an alternative power source becomes available, the terminal section 40 is able to resume with no loss of data, automatically powering itself up and reconfiguring the radio section 30 with no intervention required by the operator. After the radio section 40 has been reconfigured, it scans in the normal way for access points and re-establishes association with the network.

[0067] The terminal section 40 and the radio section 30 may also be provided with further functionality to prevent a lockup state occurring between the two sections during a suspend or power-down operation. Here the terminal section 40 interrupts the radio section 30 and commands that no wakeup operations be generated for a minimum interval (for example 1 second). During that interval, the terminal section 40 can then safely suspend or power-down. After that interval has elapsed, the radio section 30 is free to wakeup the terminal section 40 when a message is received.

[0068] The terminal section 40 and the radio section 30 may coordinate communications using a command register and an 30 interrupt. In one embodiment, the radio section 30 may include a programmable wakeup timer. The radio section 30 may then be woken up either by that timer, or by a message communicated over the airwaves and received by the radio 31, or by a command received from the terminal section 40 via the interface 34.

[0069] In order to synchronize the interface 34 the terminal section may generate one of three commands, with the radio section responding with a ready flag. The three commands are Awake for Host, Resume, and Sleep. These cause the radio section 30 to execute different actions, as described below.

[0070] In response to the Awake for Host command, the radio section 30 sets the ready flag. This allows the terminal section 40 to communicate directly with the radio section 30, to receive messages, to send messages and to process commands. In response to the Resume command, the radio section 30 turns off the ready flag to indicate that it is in an uncoordinated state, and the radio section 30 can power down whenever it decides that it has finished with communications both with the radio 31 and with the terminal section 40. In this mode, the radio section 30 will wakeup whenever a signal is received from the wakeup timer associated with the clock 35.

[0071] In response to the Sleep command, the radio section 30 stops whatever operations it may have been carrying out, in the minimum amount of time, and then goes to a low power suspend mode. When the radio section 30 receives a Resume message, it then reverts back to normal PSP mode.

[0072] It will be understood that each of the features

described above, or two or more together, may find a useful application in other types of wireless local area network and data communications system differing from the types described above.

[0073] While the invention has been illustrated and described as embodied in it is not intended to be limited to the details shown, since various modifications and structural changes may be made without departing in any way from the spirit of the present invention. 5

[0074] Without further analysis, the foregoing will so fully reveal the gist of the present invention that others can readily adapt it for various applications without omitting features that, from the standpoint of prior art, fairly constitute essential characteristics of the generic or specific aspects of this invention and, therefore, such adaptations should and are intended to be comprehended within the meaning and range of equivalence of the following claims. 10 15

[0075] According to its broadest aspect the invention relates to a method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, comprising the step of: 20 25

evaluating the mobile unit performance.
[0076] It should be noted that the objects and advantages of the invention may be attained by means of any compatible combination(s) particularly pointed out in the items of the following summary of the invention. 30

SUMMARY OF THE INVENTION

[0077] 35

1. A method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, comprising the steps of: 40

evaluating the mobile unit performance; and 45

if the mobile unit performance is below a threshold, scanning for the most eligible access point at predetermined intervals; and associating with the most eligible access point at the highest data rate. 50

2. A method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, com- 55

prising the steps of:

evaluating the mobile unit performance; and
if the mobile unit performance is below a threshold, scanning for the most eligible access point at predetermined intervals; and if the mobile unit is unable to associate with another access point at a higher data rate, reduce to data rate to the next lower data rate.

3. A method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, comprising the steps of:

evaluating the mobile unit performance; and
if the mobile unit performance is above a threshold, increasing the data rate of the mobile unit to the next highest data rate.

4. A method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, comprising the steps of:

evaluating the mobile unit performance; and
scanning for the most eligible access point at predetermined intervals;
associating with the most eligible access point at the highest data rate.

5. A method further comprising the step of transmitting a data packet from a mobile unit to an access point at a selected frequency which is one of a predetermined sequence of frequencies in a band, said selected frequency being changed at regular intervals within a repeat period.

6. A method wherein the access point transmits at predetermined intervals a beacon data packet that includes a control frame such packet being transmitted at a data rate that can be understood by all mobile units on the network.

7. A method further comprising the step of receiving said data packet at said access point at said selected frequency and synchronizing said access point in response to the data rate of the mobile unit.

8. A method wherein the step of evaluating the performance measures the percent of transmission.

9. A method wherein the step of associating with the most eligible access point is performed by selecting the access point and data rate that maximizes data throughput.

10. A data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates, and capable of communicating with at least two access points at a predetermined range therefrom, comprising:

means in the mobile unit to scan for the most eligible access point at predetermined intervals,

means in the mobile unit for evaluating the performance statistics and received access point signal quality;

means in the mobile unit to change the data rate to a second data rate; and

means for associating with the most eligible access point at the highest data rate.

11. A network wherein each mobile unit includes a transmitter for broadcasting a probe packet to all of the access points in a predetermined range from the mobile unit that is broadcasting the probe packet, said access points within said range including respective receivers for detecting the probe packet being broadcast, and for responsively sending probe response packets back to said one of the mobile units, and a selector in each of the mobile units to select a most eligible one of the access points from said probe response packets, and to associate said one of the mobile units with the most eligible one of the access points at predetermined intervals.

12. A network wherein the most eligible one of the access points is selected according to received signal quality at said one of the mobile units, and a loading factor at each of the stationary access points.

13. The network in which said one of the mobile units identifies all said stationary access points with a signal quality at least equal to a threshold value, and selects for association the most eligible one of the access points having the lowest loading factor, and in which, when a plurality of said stationary access points has an equal lowest loading factor, the stationary access point having the highest received signal quality is selected.

14. The network in which the threshold value is set below the highest received signal quality.

15. The network in which one of said plurality of the

mobile units, associated with one if said stationary access points and experiencing an unacceptably low signal quality, roams and excludes said one of the stationary access points from selection.

16. The network wherein the unacceptably low signal quality is achieved when more than 50% retries, CRC errors or missed beacons are experienced.

17. The network in which the excluded one of the stationary access points is re-included for selection when the received signal quality exceeds a predetermined limit.

18. The network in which, if none of the stationary access points is identified for re-association, said one of the mobile units continues to associate with a current one of the stationary access points.

19. The network in which each of the mobile units, associated with a current one of the stationary access points and achieving a satisfactory level of communication, makes a selection decision at selected intervals.

20. The network in which the satisfactory communication level is achieved when 50% or fewer retries, CRC errors or missed beacons are experienced.

21. The network in which an eligible group of said stationary access points is selected from all the stationary access points having a signal quality above a predetermined threshold; the group including a current one of the stationary access points having a signal quality above a further predetermined threshold; and the most eligible access point being selected from all the stationary access points having the lowest loading factor; of more than a given proportion of the loading factor of the current one of the stationary access points are excluded, and wherein, when a plurality of the stationary access points has the same loading factor, the stationary access point having the highest signal quality is selected as the most eligible access point.

Claims

1. A method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, comprising the steps of:

evaluating the mobile unit performance; and
if the mobile unit performance is below a threshold, scanning for the most eligible access

point at predetermined intervals; and associating with the most eligible access point at the highest data rate.

2. A method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, comprising the steps of:

evaluating the mobile unit performance; and if the mobile unit performance is below a threshold, scanning for the most eligible access point at predetermined intervals; and if the mobile unit is unable to associate with another access point at a higher data rate, reduce to data rate to the next lower data rate.

3. A method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, comprising the steps of:

evaluating the mobile unit performance; and if the mobile unit performance is above a threshold, increasing the data rate of the mobile unit to the next highest data rate.

4. A method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, comprising the steps of:

evaluating the mobile unit performance; and scanning for the most eligible access point at predetermined intervals; associating with the most eligible access point at the highest data rate.

5. A method as defined in claim 4, further comprising the step of transmitting a data packet from a mobile unit to an access point at a selected frequency which is one of a predetermined sequence of frequencies in a band, said selected frequency being changed at regular intervals within a repeat period.

6. A method as defined in any of the preceding claims wherein the access point transmits at predetermined intervals a beacon data packet that includes a control frame such packet being transmitted at a

data rate that can be understood by all mobile units on the network,

and/or further preferably comprising the step of receiving said data packet at said access point at said selected frequency and synchronizing said access point in response to the data rate of the mobile unit,

and/or wherein preferably the step of evaluating the performance measures the percent of transmission,

and/or wherein preferably the step of associating with the most eligible access point is performed by selecting the access point and data rate that maximizes data throughput,

7. A data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates, and capable of communicating with at least two access points at a predetermined range therefrom, comprising:

means in the mobile unit to scan for the most eligible access point at predetermined intervals,

means in the mobile unit for evaluating the performance statistics and received access point signal quality;

means in the mobile unit to change the data rate to a second data rate; and

means for associating with the most eligible access point at the highest data rate.

8. A network as defines in any of the preceding claims wherein each mobile unit includes a transmitter for broadcasting a probe packet to all of the access points in a predetermined range from the mobile unit that is broadcasting the probe packet, said access points within said range including respective receivers for detecting the probe packet being broadcast, and for responsively sending probe response packets back to said one of the mobile units, and a selector in each of the mobile units to select a most eligible one of the access points from said probe response packets, and to associate said one of the mobile units with the most eligible one of the access points at predetermined intervals,

and/or wherein preferably the most eligible one of the access points is selected according to received signal quality at said one of the mobile units, and a loading factor at each of the stationary access points,

and/or in which preferably said one of the

mobile units identifies all said stationary access points with a signal quality at least equal to a threshold value, and selects for association the most eligible one of the access points having the lowest loading factor, and in which, when a plurality of said stationary access points has an equal lowest loading factor, the stationary access point having the highest received signal quality is selected,

and/or in which preferably the threshold value is set below the highest received signal quality,

and/or in which preferably one of said plurality of the mobile units, associated with one of said stationary access points and experiencing an unacceptably low signal quality, roams and excludes said one of the stationary access points from selection.

9. The network as claimed in any of the preceding claims wherein the unacceptably low signal quality is achieved when more than 50% retries, CRC errors or missed beacons are experienced,

and/or in which preferably the excluded one of the stationary access points is re-included for selection when the received signal quality exceeds a predetermined limit,

and/or in which preferably if none of the stationary access points is identified for re-association, said one of the mobile units continues to associate with a current one of the stationary access points,

and/or in which preferably each of the mobile units, associated with a current one of the stationary access points and achieving a satisfactory level of communication, makes a selection decision at selected intervals,



and/or in which preferably the satisfactory communication level is achieved when 50% or fewer retries, CRC errors or missed beacons are experienced,


and/or in which preferably an eligible group of said stationary access points is selected from all the stationary access points having a signal quality above a predetermined threshold; the group including a current one of the stationary access points having a signal quality above a further predetermined threshold; and the most eligible access point being selected from all the stationary access points having the lowest loading factor; of more than a given proportion of the loading factor of the current one of the

stationary access points are excluded; and wherein, when a plurality of the stationary access points has the same loading factor, the stationary access point having the highest signal quality is selected as the most eligible access point.

10. A method in a data communications network including a plurality of stationary access points and a plurality of mobile units, a mobile unit being capable of transmitting at least two data rates and capable of communicating with at least two access points in a predetermined range therefrom, comprising the step of:

evaluating the mobile unit performance.





| | | | | | |
|------------|-----------------|-----------------|----------------------|----------------|--------------------------|
| AP ADDRESS | HOPPING PATTERN | PRESENT CHANNEL | TIME LEFT IN CHANNEL | LOADING FACTOR | OTHER TIMING INFORMATION |
|------------|-----------------|-----------------|----------------------|----------------|--------------------------|

FIG. 3




FIG. 5




FIG. 6

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)